

EXHIBIT 5

PID Version 9.0 – Clean



Service Performance Indicator Definitions (PID)

14-State 271 PID Version 9.0

QWEST'S SERVICE PERFORMANCE INDICATOR DEFINITIONS (PID)

14-State 271 PID Version 9.0

Introduction

Qwest will report performance results for the service performance indicators defined herein. Qwest will report separate performance results associated with the services it provides to Competitive Local Exchange Carriers (CLECs) in aggregate (except as noted herein), to CLECs individually and, as applicable, to Qwest's retail customers in aggregate. Within these categories, performance results related to service provisioning and repair will be reported for the products listed in each definition. Reports for CLECs individually will be subject to agreements of confidentiality and/or nondisclosure.

The definitions in this version of the PID apply in the 14 states of Qwest's local service region: Arizona, Colorado, Idaho, Iowa, Minnesota, Montana, Nebraska, New Mexico, North Dakota, Oregon, South Dakota, Utah, Washington and Wyoming. Individual state Performance Assurance Plans may specify and apply state specific variations from the Performance Measure definitions and/or standards contained herein.

Qwest's Service Performance Indicator Definitions

Table of Contents

ELECTRONIC GATEWAY AVAILABILITY	1
GA-1 – Gateway Availability – IMA-GUI	1
GA-2 – Gateway Availability – IMA-EDI	2
GA-3 – Gateway Availability – EB-TA	3
GA-4 – System Availability – EXACT	4
GA-6 – Gateway Availability – GUI -- Repair	5
GA-7 – Timely Outage Resolution following Software Releases	6
PRE-ORDER/ORDER	7
PO-1 – Pre-Order/Order Response Times	7
PO-2 – Electronic Flow-through	10
PO-3 – LSR Rejection Notice Interval	12
PO-4 – LSRs Rejected	13
PO-5 – Firm Order Confirmations (FOCs) On Time	14
PO-6 – Work Completion Notification Timeliness	17
PO-7 – Billing Completion Notification Timeliness	18
PO-8 – Jeopardy Notice Interval	20
PO-9 – Timely Jeopardy Notices	21
PO-15 – Number of Due Date Changes per Order	22
PO-16 – Timely Release Notifications	23
PO-19 – Stand-Alone Test Environment (SATE) Accuracy	25
PO-20 (Expanded) – Manual Service Order Accuracy	28
ORDERING AND PROVISIONING	34
OP-2 – Calls Answered within Twenty Seconds – Interconnect Provisioning Center	34
OP-3 – Installation Commitments Met	35
OP-4 – Installation Interval	38
OP-5 – New Service Quality	41
OP-6 – Delayed Days	46
OP-7 – Coordinated “Hot Cut” Interval – Unbundled Loop	49
OP-8 – Number Portability Timeliness	50
OP-13 – Coordinated Cuts On Time – Unbundled Loop	51
OP-15 – Interval for Pending Orders Delayed Past Due Date	53
OP-17 – Timeliness of Disconnects associated with LNP Orders	56
MAINTENANCE AND REPAIR	58
MR-2 – Calls Answered within 20 Seconds – Interconnect Repair Center	58
MR-3 – Out of Service Cleared within 24 Hours	59
MR-4 – All Troubles Cleared within 48 hours	61
MR-5 – All Troubles Cleared within 4 hours	63
MR-6 – Mean Time to Restore	65
MR-7 – Repair Repeat Report Rate	68
MR-8 – Trouble Rate	71
MR-9 – Repair Appointments Met	74
MR-10 – Customer and Non-Qwest Related Trouble Reports	75
MR-11 – LNP Trouble Reports Cleared within Specified Timeframes	77
BILLING	79
BI-1 – Time to Provide Recorded Usage Records	79

Table of Contents (continued)

BI-2 – Invoices Delivered within 10 Days	80
BI-3 – Billing Accuracy – Adjustments for Errors	81
BI-4 – Billing Completeness	82
DATABASE UPDATES	83
DB-1 – Time to Update Databases.....	83
DB-2 – Accurate Database Updates	85
DIRECTORY ASSISTANCE	86
DA-1 – Speed of Answer – Directory Assistance	86
OPERATOR SERVICES	87
OS-1 – Speed of Answer – Operator Services	87
NETWORK PERFORMANCE.....	88
NI-1 – Trunk Blocking	88
NP-1 – NXX Code Activation.....	90
COLLOCATION	92
CP-1 – Collocation Completion Interval.....	92
CP-2 – Collocations Completed within Scheduled Intervals.....	95
CP-3 – Collocation Feasibility Study Interval.....	98
CP-4 – Collocation Feasibility Study Commitments Met	99
DEFINITION OF TERMS	100
GLOSSARY OF ACRONYMS	104
APPENDIX A	106
<u>Feature Detail</u>	106

Electronic Gateway Availability

GA-1 – Gateway Availability – IMA-GUI

Purpose: Evaluates the quality of CLEC access to the IMA-GUI electronic gateway and one associated system, focusing on the extent they are actually available to CLECs.	
Description: GA-1A: Measures the availability of the IMA-GUI (Interconnect Mediated Access- Graphical User Interface), and reports the percentage of Scheduled Availability Time the IMA-GUI interface is available for view and/or input. <ul style="list-style-type: none"> • Scheduled Up Time hours for preorder, order, and provisioning transactions are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. GA-1D: Measures the availability of the SIA system, which facilitates access for the IMA-GUI interface and the IMA-EDI interface (see GA-2), and reports the percentage of scheduled time the SIA system is available. Scheduled availability times will be no less than the same hours as listed for IMA-GUI and IMA-EDI. <ul style="list-style-type: none"> • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., IMA-GUI, SIA), affecting Qwest’s ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level. Results will be reported as follows: GA-1A IMA Graphical User Interface Gateway GA-1D SIA system
Formula: $\left(\frac{\text{[Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period]}}{\text{[Number of Hours and Minutes of Scheduled Availability Time During Reporting Period]}} \right) \times 100$	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: <div style="text-align: center;">Available</div>	Notes:

GA-2 – Gateway Availability – IMA-EDI

Purpose: Evaluates the quality of CLEC access to the IMA-EDI electronic gateway, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of IMA-EDI (Interconnect Mediated Access - Electronic Data Interchange) interface and reports the percentage of scheduled availability time the IMA-EDI Interface is available for view and/or input. All times during which the interface is scheduled to be operating during the reporting period are measured. <ul style="list-style-type: none"> • Scheduled Up Time hours for IMA-EDI based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., IMA-EDI), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level. (See GA-1D for reporting of SIA system availability.)
Formula: $\left(\frac{[\text{Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period}]}{[\text{Number of Hours and Minutes of Scheduled Availability Time During Reporting Period}]} \right) \times 100$	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-3 – Gateway Availability – EB-TA

Purpose: Evaluates the quality of CLEC access to the EB-TA interface, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of EB-TA (Electronic Bonding – Trouble Administration) interface and reports the percentage of scheduled availability time the EB-TA Interface is available. <ul style="list-style-type: none"> • Scheduled Up Time hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., EB-TA), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level.
Formula: ([Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period] ÷ [Number of Hours and Minutes of Scheduled Availability During Reporting Period]) x 100	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-4 – System Availability – EXACT

<p>Purpose: Evaluates the quality of CLEC batch access to the EXACT electronic access service request system, focusing on the extent the system is actually available to CLECs.</p>	
<p>Description: Measures the availability of EXACT system and reports the percentage of scheduled availability time the EXACT system is available.</p> <ul style="list-style-type: none"> • Scheduled Up Time hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. • Time System is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the system is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., EXACT), affecting Qwest's ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC aggregate results</p>	<p>Disaggregation Reporting: Region-wide level.</p>
<p>Formula: $\left(\frac{[\text{Number of Hours and Minutes EXACT is Available to CLECs During Reporting Period}]}{[\text{Number of Hours and Minutes of Scheduled Availability During Reporting Period}]} \right) \times 100$ </p>	
<p>Exclusions: None</p>	
<p>Product Reporting: None</p>	<p>Standard: 99.25 percent</p>
<p>Availability: Available</p>	<p>Notes:</p>

GA-6 – Gateway Availability – GUI – Repair

Purpose: Evaluates the quality of CLEC access to the GUI Repair electronic gateway, focusing on the extent the gateway is actually available to CLECs.	
Description: Measures the availability of the GUI (Graphical User Interface) repair electronic interface and reports the percentage of scheduled availability time the interface is available for view and/or input. All times during which the interface is scheduled to be operating during the reporting period are measured. <ul style="list-style-type: none"> • Scheduled Up Time” hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. • Time Gateway is Available to CLECs is equal to Scheduled Availability Time minus Outage Time. • Scheduled Availability Time is equal to Scheduled Up Time minus Scheduled Down Time. • Scheduled Down Time is time identified and communicated that the interface is not available due to maintenance and/or upgrade work. Notification of Scheduled Down Time for routine maintenance and/or upgrade work will be provided no less than 48 hours in advance. • An outage is a critical or serious loss of functionality, attributable to the specified gateway or component (i.e., GUI-Repair), affecting Qwest’s ability to serve its customers. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. 	
Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate results	Disaggregation Reporting: Region-wide level.
Formula: [Number of Hours and Minutes Gateway is Available to CLECs During Reporting Period ÷ Number of Hours and Minutes of Scheduled Availability Time During Reporting Period] x 100	
Exclusions: None	
Product Reporting: None	Standard: 99.25 percent
Availability: Available	Notes:

GA-7 – Timely Outage Resolution following Software Releases

<p>Purpose: Measures the timeliness of resolution of gateway or system outages attributable to software releases for specified OSS interfaces, focusing on CLEC-affecting software releases involving the specified gateways or systems.</p>	
<p>Description:</p> <ul style="list-style-type: none"> Measures the percentage of gateway or system outages, which are attributable to OSS system software releases and which occur within two weeks after the implementation of the OSS system software releases, that are resolved ^{NOTE 1} within 48 hours of detection by the Qwest monitoring group or reporting by a CLEC/co-provider. Includes software releases associated with the following OSS interfaces in Qwest: IMA-GUI, IMA-EDI, and CEMR, Exchange Access, Control, & Tracking (EXACT) ^{NOTE 2}, Electronic Bonding– Trouble Administration (EB -TA) ^{NOTE 3} An outage for this measurement is a critical or serious loss of functionality, attributable to the specified gateway or component, affecting Qwest’s ability to serve its customers or data loss ^{NOTE 4} on the Qwest side of the interface. An outage is determined by Qwest technicians through the use of verifiable data, collected from the affected customer(s) and/or from mechanized event management systems. The outage resolution time interval considered in this measurement starts at the time Qwest’s monitoring group detects a failure, or at the date/time of the first transaction sent to Qwest that cannot be processed (i.e. lost data), and ends with the time functionality is restored or the lost data is recovered. 	
<p>Reporting Period: Monthly</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC Aggregate</p>	<p>Disaggregation Reporting: Region-wide level.</p>
<p>Formula: $\left[\frac{\text{Total outages detected within two weeks of a Software Release that are resolved within 48 hours of the time Qwest detects the outage}}{\text{Total number of outages detected within two weeks of Software Releases resolved in the Reporting Period}} \right] \times 100$</p>	
<p>Exclusions:</p> <ul style="list-style-type: none"> Outages in releases prior to any CLEC migrating to the release. Duplicate reports attributable to the same software defect. 	
<p>Product Reporting: None</p>	<p>Standards:</p> <p>Volume = 1-20: 1 miss Volume > 20: 95%</p>
<p>Availability:</p> <p>Available</p>	<p>Notes:</p> <ol style="list-style-type: none"> “Resolved” means that service is restored to the reporting CLEC, as experienced by the CLEC. EXACT is a Telecordia system. Only releases for changes initiated by Qwest for hardware or connectivity will be included in this measurement. Outages reported under EB-TA are the same as outages in MEDIACC. For data loss to be considered for GA-7, a functional acknowledgement must have been provided for the data in question (e.g., EDI 997, LSR ID or trouble ticket number).

Pre-Order/Order

PO-1 – Pre-Order/Order Response Times

Purpose:

Evaluates the timeliness of responses to specific preordering/ordering queries for CLECs through the use of Qwest's Operational Support Systems (OSS). Qwest's OSS are accessed through the specified gateway interface.

Description:**PO-1A & PO-1B:**

Measures the time interval between query and response for specified pre-order/order transactions through the electronic interface.

- Measurements are made using a system that simulates the transactions of requesting pre-ordering/ordering information from the underlying existing OSS. These simulated transactions are made through the operational production interfaces and existing systems in a manner that reflects, in a statistically-valid manner, the transaction response times experienced by CLEC service representatives in the reporting period.
- The time interval between query and response consists of the period from the time the transaction request was "sent" to the time it is "received" via the gateway interface.
- A query is an individual request for the specified type of information.

PO-1C:

- Measures the percentage of all IRTM Queries measured by PO-1A & 1B transmitted in the reporting period that timeout before receiving a response.

PO-1D:

- Measures the average response time for a sampling of rejected queries across preorder transaction types. The response time measured is the time between the issuance of a pre-ordering transaction and the receipt of an error message associated with a "rejected query." A rejected query is a transaction that cannot be successfully processed due to the provision of incomplete or invalid information by the sender, which results in an error message back to the sender. ^{NOTE 1}

Reporting Period: One month**Unit of Measure:**

PO-1A, PO-1B, & PO-1D: Seconds
PO-1C: Percent

PO-1 – Pre-Order/Order Response Times (continued)

<p>Reporting Comparisons: CLEC aggregate.</p>	<p>Disaggregation Reporting: Region-wide level. Results are reported as follows: PO-1A Pre-Order/Order Response Time for IMA-GUI PO-1B Pre-Order/Order Response Time for IMA-EDI</p> <p>Results are reported separately for each of the following transaction types: ^{NOTE 2}</p> <ol style="list-style-type: none"> 1. Appointment Scheduling (Due Date Reservation, where appointment is required) 2. Service Availability Information 3. Facility Availability 4. Street Address Validation 5. Customer Service Records 6. Telephone Number 7. Loop Qualification Tools ^{NOTE 3} 8. Left intentionally blank to preserve numbering 9. Connecting Facility Assignment ^{NOTE 4} 10. Meet Point Inquiry ^{NOTE 5} <p>For PO-1A (transactions via IMA-GUI), in addition to reporting total response time, response times for each of the above transactions will be reported in two parts: (a) time to access the request screen, and (b) time to receive the response for the specified transaction. For PO-1A 6, Telephone Number, a third part (c) accept screen, will be reported.</p> <p>For PO-1B (transactions via IMA-EDI), request/response will be reported as a combined number.</p> <p>PO-1C Results for PO-1C will be reported according to the gateway interface used:</p> <ol style="list-style-type: none"> 1. Percent of Preorder Transactions that Timeout IMA-GUI 2. Percent of Preorder Transactions that Timeout IMA-EDI <p>PO-1D Results for PO-1D will be reported according to the gateway interface used:</p> <ol style="list-style-type: none"> 1. Rejected Response Times for IMA-GUI 2. Rejected Response Times for IMA-EDI
<p>Formula:</p> <p>PO-1A & PO-1B = $\frac{\sum[(\text{Query Response Date \& Time}) - (\text{Query Submission Date \& Time})]}{(\text{Number of Queries Submitted in Reporting Period})}$</p> <p>PO-1C = $\frac{[(\text{Number of IRTM Queries measured by PO-1A \& 1B that Timeout before receiving response}) \div (\text{Number of IRTM Queries Transmitted in Reporting Period})]}{1} \times 100$</p> <p>PO-1D = $\frac{\sum[(\text{Rejected Query Response Date \& Time}) - (\text{Query Submission Date \& Time})]}{(\text{Number of Rejected Query Transactions Simulated by IRTM})}$</p>	
<p>Exclusions:</p> <p>PO-1A & PO-1B:</p> <ul style="list-style-type: none"> • Rejected requests/errors, and timed out transactions <p>PO-1C:</p> <ul style="list-style-type: none"> • Rejected requests and errors <p>PO-1D:</p> <ul style="list-style-type: none"> • Timed out transactions 	

PO-1 – Pre-Order/Order Response Times (continued)

Product Reporting: None	Standards: Total Response Time:	IMA-GUI	IMA-EDI
	1. Appointment Scheduling	<10 seconds	<10 seconds
	2. Service Availability Information	<25 seconds	<25 seconds
	3. Facility Availability	<25 seconds ⁶	<25 seconds ⁶
4. Street Address Validation	<10 seconds	<10 seconds	
5. Customer Service Records	<12.5 seconds ⁶	<12.5 seconds ⁶	
6. Telephone Number	<10 seconds	<10 seconds	
7. Loop Qualification Tools <small>NOTE³</small>	≤ 20 seconds ⁷	≤ 20 seconds	
8. Left intentionally blank to preserve numbering			
9. Connecting Facility Assignment	≤ 25 seconds	≤ 25 seconds	
10. Meet Point Inquiry	≤ 30 seconds	≤ 30 seconds	
PO-1C-1	0.5%		
PO-1C-2	0.5%		
PO-1D-1 & 2	Diagnostic		
Availability: Available	Notes: <ol style="list-style-type: none"> 1. Rejected query types used in PO-1D are those developed for internal Qwest diagnostic purposes. 2. As additional transactions, currently done manually, are mechanized, they will be measured and added to or included in the above list of transactions, as applicable. 3. Results based on a weighted combination of ADSL Loop Qualification and Raw Loop Data Tool. 4. Results based on Connecting Facility Assignment by Unit Query. 5. Results based on meet Point Query, POTS Splitter option for Shared loops. 6. Times reflect non-complex services, including residential, simple business, or POTS account. Does not include ADSL or accounts>25 lines. 7. Benchmark applies to response time only. Request time and Total time will also be reported. 		

PO-2 – Electronic Flow-through

<p>Purpose: Monitors the extent Qwest's processing of CLEC Local Service Requests (LSRs) is completely electronic, focusing on the degree that electronically-transmitted LSRs flow directly to the service order processor without human intervention or without manual retyping.</p>	
<p>Description: PO-2A - Measures the percentage of all electronic LSRs that flow from the specified electronic gateway interface to the Service Order Processor (SOP) without any human intervention.</p> <ul style="list-style-type: none"> • Includes all LSRs that are submitted electronically through the specified interface during the reporting period, subject to exclusions specified below. <p>PO-2B – Measures the percentage of all flow-through-eligible LSRs ^{NOTE 1} that flow from the specified electronic gateway interface to the SOP without any human intervention.</p> <ul style="list-style-type: none"> • Includes all flow-through-eligible LSRs that are submitted electronically through the specified interface during the reporting period, subject to exclusions specified below. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC aggregate, individual CLEC</p>	<p>Disaggregation Reporting: Statewide level (per multi-state system serving the state). Results for PO-2A and PO-2B will be reported according to the gateway interface* used to submit the LSR:</p> <ol style="list-style-type: none"> 1 LSRs received via IMA-GUI 2 LSRs received via IMA-EDI <p>*CO also reports an aggregate of IMA-GUI and IMA-EDI results.</p>
<p>Formula: PO-2A = $\frac{[(\text{Number of Electronic LSRs that pass from the Gateway Interface to the SOP without human intervention}) \div (\text{Total Number of Electronic LSRs that pass through the Gateway Interface})] \times 100}{}$</p> <p>PO-2B = $\frac{[(\text{Number of flow-through-eligible Electronic LSRs that actually pass from the Gateway Interface to the SOP without human intervention}) \div (\text{Number of flow-through-eligible Electronic LSRs received through the Gateway Interface})] \times 100}{}$</p>	
<p>Exclusions:</p> <ul style="list-style-type: none"> • Rejected LSRs and LSRs containing CLEC-caused non-fatal errors. • Non-electronic LSRs (e.g., via fax or courier). • Records with invalid product codes. • Records missing data essential to the calculation of the measurement per the PID. • Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.) • Invalid start/stop dates/times. 	

PO-2 – Electronic Flow-through (continued)

Product Reporting: <ul style="list-style-type: none"> • Resale • Unbundled Loops (with or without Local Number Portability) • Local Number Portability • UNE-P (POTS) and UNE-P (Centrex 21) • Line Sharing 	Standards: <u>PO-2A:</u> Diagnostic <u>PO-2B:</u>	
	Resale:	95%
	Unbundled Loops:	85%
	LNP:	95%
	UNE-P (POTS & Centrex 21):	95%
Availability: Available	Notes: <ol style="list-style-type: none"> 1. The list of LSR types classified as eligible for flow through is contained in the “LSRs Eligible for Flow Through” matrix. This matrix also includes availability for enhancements to flow through. Matrix will be distributed through the CMP process. 2. The standard and future disaggregated reporting of the Line Sharing product is TBD, pending resolution of TRO issues. 	
	Line Sharing:	Diagnostic ^{NOTE 2}

PO-3 – LSR Rejection Notice Interval

<p>Purpose: Monitors the timeliness with which Qwest notifies CLECs that electronic and manual LSRs were rejected.</p>	
<p>Description: Measures the interval between the receipt of a Local Service Request (LSR) and the rejection of the LSR for standard categories of errors/reasons.</p> <ul style="list-style-type: none"> • Includes all LSRs submitted through the specified interface that are rejected during the reporting period. • Standard reasons for rejections are: missing/incomplete/mismatching/unintelligible information, duplicate request or LSR/PON (purchase order number), no separate LSR for each account telephone number affected, no valid contract, no valid end user verification, account not working in Qwest territory, service-affecting order pending, request is outside established parameters for service, and lack of CLEC response to Qwest question for clarification about the LSR. • Included in the interval is time required for efforts by Qwest to work with the CLEC to avoid the necessity of rejecting the LSR. • With hours: minutes reporting, hours counted are (1) business hours for manual rejects (involving human intervention) and (2) published Gateway Availability hours for auto-rejects (involving no human intervention). Business hours are defined as time during normal business hours of the Wholesale Delivery Service Centers, except for PO-3C in which hours counted are workweek clock hours. Gateway Availability hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: PO-3A-1, PO-3B-1 & PO-3C - Hrs: Mins. PO-3A-2 & PO-3B-2 – Mins: Secs.</p>
<p>Reporting Comparisons: CLEC aggregate and individual CLEC results</p>	<p>Disaggregation Reporting: Results for this indicator are reported according to the gateway interface used to submit the LSR:</p> <ul style="list-style-type: none"> • PO-3A-1, LSRs received via IMA-GUI and rejected manually: Statewide • PO-3A -2, LSRs received via IMA-GUI and auto-rejected: Region wide • PO-3B-1, LSRs received via IMA-EDI and rejected manually: Statewide • PO-3B -2, LSRs received via IMA-EDI and auto-rejected: Region wide • PO-3C, LSRs received via facsimile: Statewide
<p>Formula: $\Sigma [(Date\ and\ time\ of\ Rejection\ Notice\ transmittal) - (Date\ and\ time\ of\ LSR\ receipt)] \div (Total\ number\ of\ LSR\ Rejection\ Notifications)$</p>	
<p>Exclusions:</p> <ul style="list-style-type: none"> • Records with invalid product codes. • Records missing data essential to the calculation of the measurement per the PID. • Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.) • Invalid start/stop dates/times. 	
<p>Product Reporting: Not applicable (reported by ordering interface).</p>	<p>Standards:</p> <ul style="list-style-type: none"> • PO-3A-1 and -3B-1: ≤ 12 business hours • PO-3A -2 and -3B -2: ≤ 18 seconds • PO-3C: ≤ 24 work week clock hours
<p>Availability: Available</p>	<p>Notes:</p>

PO-4 – LSRs Rejected

<p>Purpose: Monitors the extent LSRs are rejected as a percentage of all LSRs to provide information to help address potential issues that might be raised by the indicator of LSR rejection notice intervals.</p>	
<p>Description: Measures the percentage of LSRs rejected (returned to the CLEC) for standard categories of errors/reasons.</p> <ul style="list-style-type: none"> • Includes all LSRs submitted through the specified interface that are rejected or FOC'd during the reporting period. • Standard reasons for rejections are: missing/incomplete/mismatching/unintelligible information; duplicate request or LSR/PON (purchase order number); no separate LSR for each account telephone number affected; no valid contract; no valid end user verification; account not working in Qwest territory; service-affecting order pending; request is outside established parameters for service; and lack of CLEC response to Qwest question for clarification about the LSR. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent of LSRs</p>
<p>Reporting Comparisons: CLEC aggregate and individual CLEC results</p>	<p>Disaggregation Reporting: Results for this indicator are reported according to the gateway interface used to submit the LSR:</p> <ul style="list-style-type: none"> PO-4A-1 LSRs received via IMA-GUI and rejected manually – Region wide PO-4A -2 LSRs received via IMA-GUI and auto-rejected – Region wide PO-4B-1 LSRs received via IMA-EDI and rejected manually – Region wide PO-4B -2 LSRs received via IMA-EDI and auto-rejected – Region wide PO-4C LSRs received via facsimile – Statewide
<p>Formula: [(Total number of LSRs rejected via the specified method in the reporting period) ÷ (Total of all LSRs that are received via the specified interface that were rejected or FOC'd in the reporting period)] x 100</p>	
<p>Exclusions:</p> <ul style="list-style-type: none"> • Records with invalid product codes. • Records missing data essential to the calculation of the measurement per the PID. • Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.) • Invalid start/stop dates/times. 	
<p>Product Reporting: Not applicable (reported by ordering interface).</p>	<p>Standard: Diagnostic</p>
<p>Availability: Available</p>	<p>Notes:</p>

PO-5 – Firm Order Confirmations (FOCs) On Time

<p>Purpose: Monitors the timeliness with which Qwest returns Firm Order Confirmations (FOCs) to CLECs in response to LSRs/ASRs received from CLECs, focusing on the degree to which FOCs are provided within specified intervals.</p>	
<p>Description: Measures the percentage of Firm Order Confirmations (FOCs) that are provided to CLECs within the intervals specified under “Standards” below for FOC notifications.</p> <ul style="list-style-type: none"> • Includes all LSRs/ASRs that are submitted through the specified interface or in the specified manner (i.e., facsimile) that receive an FOC during the reporting period, subject to exclusions specified below. (Acknowledgments sent separately from an FOC (e.g., EDI 997 transactions are not included.) • For PO-5A, the interval measured is the period between the LSR received date/time (based on scheduled up time) and Qwest’s response with a FOC notification (notification date and time). • For PO-5B, 5C, and 5D, the interval measured is the period between the <u>application date and time</u>, as defined herein, and Qwest’s response with a FOC notification (notification date and time). • “Fully electronic” LSRs are those (1) that are received via IMA-GUI or IMA-EDI, (2) that involve no manual intervention, and (3) for which FOCs are provided mechanically to the CLEC. ^{NOTE 2} • “Electronic/manual” LSRs are received electronically via IMA-GUI or IMA-EDI and involve manual processing. • “Manual” LSRs are received manually (via facsimile) and processed manually. • ASRs are measured only in <u>business days</u>. • LSRs will be evaluated according to the FOC interval categories shown in the “Standards” section below, based on the number of lines/services requested on the LSR or, where multiple LSRs from the same CLEC are related, based on the combined number of lines/services requested on the related LSRs. 	
<p>Reporting Period: One month</p>	<p>Unit of Measure: Percent</p>
<p>Reporting Comparisons: CLEC aggregate and individual CLEC results</p>	<p>Disaggregation Reporting: Statewide level (per multi-state system serving the state). Results for this indicator are reported as follows:</p> <ul style="list-style-type: none"> • PO-5A:* FOCs provided for <u>fully electronic</u> LSRs received via: <ul style="list-style-type: none"> – PO-5A-1 IMA-GUI – PO-5A-2 IMA-EDI • PO-5B:* FOCs provided for <u>electronic/manual</u> LSRs received via: <ul style="list-style-type: none"> – PO-5B-1 IMA-GUI – PO-5B-2 IMA-EDI • PO-5C:* FOCs provided for <u>manual</u> LSRs received via Facsimile. • PO-5D: FOCs provided for ASRs requesting LIS Trunks. <p>* Each of the PO-5A, PO-5B and PO-5C measurements listed above will be further disaggregated as follows:</p> <ul style="list-style-type: none"> – (a) FOCs provided for Resale services and UNE-P – (b) FOCs provided for Unbundled Loops and specified Unbundled Network Elements – (c) FOCs provided for LNP
<p>Formula: $PO-5A = \{[\text{Count of LSRs for which the original FOC's "(FOC Notification Date \& Time) - (LSR received date/time (based on scheduled up time))" is within 20 minutes}] \div (\text{Total Number of original FOC Notifications transmitted for the service category in the reporting period})\} \times 100$ $PO-5B, 5C, \& 5D = \{[\text{Count of LSRs/ASRs for which the original FOC's "(FOC Notification Date \& Time) - (Application Date \& Time)" is within the intervals specified for the service category involved}] \div (\text{Total Number of original FOC Notifications transmitted for the service category in the reporting period})\} \times 100$</p>	

PO-5 – Firm Order Confirmations (FOCs) On Time (continued)

Exclusions:

- LSRs/ASRs involving individual case basis (ICB) handling based on quantities of lines, as specified in the “Standards” section below, or service/request types, deemed to be projects.
- Hours on Weekends and holidays. (Except for PO-5A which only excludes hours outside the scheduled up time).
- LSRs with CLEC-requested FOC arrangements different from standard FOC arrangements.
- Records with invalid product codes.
- Records missing data essential to the calculation of the measurement per the PID.
- Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.)
- Invalid start/stop dates/times.

Additional PO-5D exclusion:

- Records with invalid application or confirmation dates.

<p>Product Reporting:</p> <ul style="list-style-type: none"> • For PO-5A, -5B and -5C: <ul style="list-style-type: none"> (a) Resale services UNE-P (POTS) and UNE-P Centrex (b) Unbundled Loops and specified Unbundled Network Elements. (c) LNP • For PO-5D: LIS Trunks. 	Standards:	
	• For PO-5A (all):	95% within 20 minutes ^{NOTE 2}
	• For PO-5B (all):	90% within standard FOC intervals (specified below)
	• For PO-5C (manual):	90% within standard FOC intervals specified below PLUS 24 hours ^{NOTE 3}
	• For PO-5D (LIS Trunks):	85% within eight business days
	<u>Standard FOC Intervals for PO-5B and PO-5C</u>	
	Product Group ^{NOTE 1}	FOC Interval
	Resale	
	Residence and Business POTS	1-39 lines
	ISDN-Basic	1-10 lines
– Conversion As Is		
– Adding/Changing features		
– Add primary directory listing to established loop		
– Add call appearance		
Centrex Non-Design	1-19 lines	
with no Common Block Configuration		
Centrex line feature changes/adds/removals (all)		
LNP	1-24 lines	
Unbundled Loops		
2/4 Wire analog	1-24 loops	
DS3 Capable		
Sub-loop	1-24 sub-loops	
[included in Product Reporting group (b)]		
Line Sharing/Line Splitting/Loop Splitting		
	1-24 shared loops	
[included in Product Reporting group (b)]		
Unbundled Network Element–Platform (UNE-P POTS)		
	1 – 39 lines	

PO-5 – Firm Order Confirmations (FOCs) On Time (continued)

	Resale ISDN-Basic 1-10 lines – Conversion As Specified – New Installs – Address Changes – Change to add Loop ISDN-PRI (Facility) 1-3 PBX 1-24 trunks DS0 or Voice Grade Equivalent 1-24 DS1 Facility 1-24 DS3 Facility 1-3	48 hours
	LNP 25-49 lines	
	Enhanced Extended Loops (EELs) [included in Product Reporting group (b)] DS1 1-24 circuits	
	Resale Centrex (including Centrex 21, Non-design, Centrex 21 Basic ISDN, Centrex-Plus, Centron, Centrex Primes) 1-10 lines – With Common Block Configuration required – Initial establishment of Centrex CMS services – Tie lines or NARs activity – Subsequent to initial Common Block – Station lines – Automatic Route Selection – Uniform Call Distribution – Additional numbers	72 hours
	UNE-P Centrex 1-10 lines	
	UNE-P Centrex 21 1-10 lines	
	Unbundled Loops with Facility Check ^(NOTE 2, 3) 1 – 24 loops 2/4 wire Non-loaded ADSL compatible ISDN capable XDSL-I capable DS1 capable	
	Resale ISDN-PRI (Trunks) 1-12 trunks	96 hours
	For PO-5D: LIS Trunks 1-240 trunk circuits	8 business days
	Availability: Available	Notes: 1. LSRs with quantities above the highest number specified for each product type are considered ICB. 2. Unbundled Loop with Facility Check can be processed electronically; however, because this category always carries a 72-hour FOC interval the FOC results for this product will appear in PO-5B if received electronically or PO-5C if received manually. 3. Unbundled Loop with Facility Check will not add an additional 24 hours to the 72-hour interval if the LSR is submitted manually.

PO-6 – Work Completion Notification Timeliness

Purpose: To evaluate the timeliness of Qwest issuing electronic notification at an LSR level to CLECs that provisioning work on all service orders that comprise the CLEC LSR have been completed in the Service Order Processor and the service is available to the customer.	
Description: PO-6A & 6B: <ul style="list-style-type: none"> • Includes all orders completed in the Qwest Service Order Processor that generate completion notifications in the reporting period, subject to exclusions shown below. • The start time is the date/time when the last of the service orders that comprise the CLEC LSR is posted as completed in the Service Order Processor. • The end time is when the electronic order completion notice is made available (IMA-GUI) ^{NOTE 1} or transmitted (IMA-EDI) to the CLEC via the ordering interface used to place the local service request. The notification is transmitted at an LSR level when all service orders that comprise the CLEC LSR are complete. • With hours: minutes reporting, hours counted are during the published Gateway Availability hours. Gateway Availability hours are based on the currently published hours of availability found on the following website: http://www.qwest.com/wholesale/cmp/ossHours.html. 	
Reporting Period: One month	Unit of Measure: PO-6A - 6B: Hrs:Mins
Reporting Comparisons: CLEC aggregate and individual CLEC results.	Disaggregation Reporting: Statewide level. <ul style="list-style-type: none"> • PO-6A Notices transmitted via IMA-GUI • PO-6B Notices transmitted via IMA-EDI
Formula: <u>For completion notifications generated from LSRs received via IMA-GUI:</u> $PO-6A = \Sigma((\text{Date and Time Completion Notification made available to CLEC}) - (\text{Date and Time the last of the service orders that comprise the CLEC LSR is completed in the Service Order Processor})) \div (\text{Number of completion notifications made available in reporting period})$ <u>For completion notifications generated from LSRs received via IMA-EDI:</u> $PO-6B = \Sigma((\text{Date and Time Completion Notification transmitted to CLEC}) - (\text{Date and Time the last of the service orders that comprise the CLEC LSR is completed in the Service Order Processor.})) \div (\text{Number of completion notifications transmitted in reporting period})$	
Exclusions: PO – 6A & 6B: <ul style="list-style-type: none"> • Records with invalid completion dates. • LSRs submitted manually (e.g., via facsimile). • ASRs submitted via EXACT. 	
Product Reporting: PO – 6A & 6B Aggregate reporting for all products ordered through IMA-GUI and, separately, IMA-EDI (see disaggregation reporting).	Standard: 6 hours
Availability: Available	Notes: 1. The time a notice is “made available” via the IMA-GUI is the time Qwest stores a status update related to the completion notice in the IMA Status Updates database. When this occurs, the notice can be immediately viewed by the CLEC using the Status Updates window or by using the LSR Notice Inquiry function.

